



GUANGZHOU LEILA TRADING CO., LTD

ADD: 913, WEST TOWER, PEARL RIVER BUILDING, NO.360 RING EAST ROAD,
YUEXIU DISTRICT, GUANGZHOU CHNA

MOB: +86 198 6610 5902

TEL: +86 (020) 8376 7362

E-MAIL: mag@gz-leila.com

WEB: <https://gz-leila.com/>

Technical Data Sheet

Processing aids K138T

Overview

The acrylic processing aid K138T produced by our company is suitable for the production and processing of PVC rigid foam products.

Application

This product exhibits a relatively balanced plasticizing and homogenizing effect, effectively enhancing the dispersion of PVC dry powder in the extruder and overall improving the physical-mechanical properties and surface brightness of PVC extruded products. For PVC rigid foam products, it can significantly enhance the fineness and uniformity of foam cell structures. This product is particularly suitable for the production and processing of PVC wood-plastic foam building materials, PVC rigid profiles, PVC advertising boards, decorative panels, wall panels, WPC flooring, as well as PVC foam products such as air windows and blinds.

Appearance

Whiter powder

Specification

Item	Index	Unit
Heating Reduction	≤ 1.5	%
Apparent density	0.3-0.6	g/ml ³
Intrinsic viscosity	14-16	dL/g

Application Parameters

Suggested Dosage	0.5-3.0	%
------------------	---------	---

Health Performance

Satisfy the specific requirements of ROHS.

Remark

Should be transported in accordance with regulations of non-dangerous goods and stored in a ventilated and dry warehouse.

Package

Packaged in PE woven bags, with a net weight of 25KG per bag.