



GUANGZHOU LEILA TRADING CO., LTD

ADD: 913, WEST TOWER, PEARL RIVER BUILDING, NO.360 RING EAST ROAD,
YUEXIU DISTRICT, GUANGZHOU CHNA

MOB: +86 198 6610 5902

TEL: +86 (020) 8376 7362

E-MAIL: mag@gz-leila.com

WEB: <https://gz-leila.com/>

Technical Data Sheet

Stabilizer CZ3366L

Overview

The environmentally friendly calcium zinc stabilizer CZ3366L produced by our company is suitable for the production and processing of ABA co extruded flooring, carbon crystal board, WPC flooring, crash board and other products.

Application

CZ3366L calcium zinc stabilizer is suitable for processing ABA co extruded flooring, carbon crystal board, WPC flooring, anti-collision board and other products. This product has balanced thermal stability, which can ensure consistent thermal stability of the surface, core, and bottom layers during co extrusion, avoiding problems such as uneven thermal decomposition and color difference. Assist in achieving uniform wall thickness and precise size of the product, effectively enhancing interlayer bonding and preventing delamination. The product has excellent comprehensive performance, good production stability, smooth surface, and a wide range of applications.

Appearance

White microbeads or powder

Specification

Item	Index	Unit
Heating reduction:	≤ 2.0	%
Initial melting point:	≥ 65	°C
Processing temperature:	150-200	°C

Application Parameters

Suggested Dosage:	1.0-1.5	% (Calculated per 25kg resin)
-------------------	---------	-------------------------------

Health Performance

Satisfy the specific requirements of ROHS.

Remark

Should be transported in accordance with regulations of non-dangerous goods and stored in a ventilated and dry warehouse.

Package

Packaged in PE woven bags, with a net weight of 25KG per bag.